



## REWORK FLUX WS

**WATER SOLUBLE!!!**

Type ISO 1.2.3.C

Solder Chemistry Rework Flux has been developed especially for all SMT-repairs. Also it could be used for all other known manual soldering applications. The Rework Flux is a flux based on special rosins, detergents and includes a composition of halogen free activators. This basis guarantees the very best cleaning abilities and the superior soldering results. Minimal highly transparent residues, after soldering, can be easily washed away after days and also have to be washed away!

### PHYSICAL PROPERTIES:

Density : ca. 1.0 g/cm<sup>3</sup>

Solid content: ca. 78%

PH-value : ca. 4-5

**VISCOSITY** (Pa.s) +/-10% measured with Brookfield RVT-DV-II

At 25°C comes to 165.

### STORAGE

At room temperature 6 months

### APPLICATION

The Rework Flux has been designed generally for applications by syringes, but it is suitable for all other kinds of dosages. **The complete removal of the residues is necessary and can be done simply by using clear water without additives!**

### PACKING

Syringes: 5ccm, 10ccm and 30ccm

Solder Chemistry ; Fragnerstraße 4 ; D-84034 Landshut

Tel. ++49/871/4309500 ; Fax. ++49/871/43095020

e-Mail: [info@SolderChemistry.com](mailto:info@SolderChemistry.com) ; [www.SolderChemistry.com](http://www.SolderChemistry.com)

The engineering data shown here has been compiled by producer using commonly accepted procedures. Although the data is considered accurate, we cannot guarantee its accuracy, the results obtained from its use, or any patent infringement resulting from its use. The data is supplied on the condition that the user shall conduct tests to determine material suitability for a particular application